


Ficha técnica



SPLIT 1X1
IX90S ION



Plasma generador de iones



		PVP TARIFA 2020	455€	475€	910€	1.160€
		HTWS026IX90SION	HTWS035IX90SION	HTWS052IX90SION	HTWS071IX90SION	HTWS071IX90SION
MODELO	INT. EXT.	HTWS026IX90SION-I HTWS026IX90SION-O	HTWS035IX90SION-I HTWS035IX90SION-O	HTWS052IX90SION-I HTWS052IX90SION-O	HTWS071IX90SION-I HTWS071IX90SION-O	HTWS071IX90SION-I HTWS071IX90SION-O
Alimentación eléctrica	V,F,HZ	220-240V (1 Fase ~ 50Hz)				
RENDIMIENTO						
Capacidad refrigeración	Capacidad (mín.-máx.)	W	2.500 (400 - 2.900)	3.400 (550 - 3.900)	5.270 (1.000 - 6.700)	6.450 (1.400 - 7.000)
		Btu/h	8.530 (1.365 - 9.895)	11.600 (1.877 - 13.310)	17.981 (3.412 - 22.860)	22.007 (4.777 - 23.884)
	Consumo (mín.-máx.)	W	750 (150 - 1.430)	1.020 (180 - 1.560)	1.540 (320 - 2.460)	1.840 (380 - 2.800)
	SEER	-	6,1	6,1	6,3	6,4
Capacidad calefacción	Clasificación energética	Frío	A++	A++	A++	A++
	Capacidad (mín.-máx.)	kW	2.800 (400 - 3.300)	3.600 (600 - 4.200)	5.500 (1.100 - 6.800)	6.600 (1.500 - 7.900)
		Btu/h	9.554 (1.365 - 11.260)	12.280 (2.047 - 17.330)	18.766 (3.753 - 23.202)	22.519 (5.118 - 26.955)
	Consumo (mín.-máx.)	W	775 (135 - 1.550)	995 (140 - 1.650)	1.480 (350 - 2.300)	1.750 (400 - 2.500)
	SCOP	-	4	4	4	4
	Clasificación energética	Calor	A+	A+	A+	A+
CARACTERÍSTICAS						
Unidad interior	Potencia sonora (SH/H/L/SL)	dB(A)	54/39/36/30	55/40/37/31	58/55/42/40	61/57/48/46
	Presión sonora (SH/H/L/SL)	dB(A)	40/36/24/19	41/37/25/20	47/44/31/29	48/44/35/33
	Caudal de aire (SH/H/L/SL)	m³/h	520/440/230/150	550/470/250/180	850/760/570/480	1.090/930/670/560
	Rango temperatura seleccionable	°C	16 ~ 31	16 ~ 31	16 ~ 31	16 ~ 31
Unidad exterior	Potencia sonora	dB(A)	61	62	63	68
	Presión sonora	dB(A)	52	53	55	59
	Caudal de aire	m³/h	1.800	1.800	2.800	3.300
	Temperatura de funcionamiento frío / calor	°C	(-15 ~ 43) / (-15 ~ 24)	(-15 ~ 43) / (-15 ~ 24)	(-15 ~ 43) / (-15 ~ 24)	(-15 ~ 43) / (-15 ~ 24)
Refrigerante	Compresor		Sanyo	Sanyo	Panasonic	Panasonic
	Tipo/Carga	R32/Kg	0,5	0,7	0,9	1,0
	Carga adicional >5	g/m	16	16	16	40
DIMENSIONES Y PESO						
Unidad interior	Dimensiones netas (AnxAlxPr)	mm	821x283x200	821x283x200	1003x310x222	1109x331x250
	Dimensiones brutas (AnxAlxPr)		898x291x353	898x291x353	1080x314x383	1181x354x417
	Peso neto/bruto	Kg	9 / 11	9 / 11	14 / 16,5	16,5 / 19,5
Unidad exterior	Dimensiones netas (AnxAlxPr)	mm	830x540x325	830x540x325	890x598x372	960x700x396
	Dimensiones brutas (AnxAlxPr)		879x605x366	879x605x366	941x663x412	1011x763x455
	Peso neto/bruto	Kg	27 / 29,5	29 / 31,5	40 / 43	43,5 / 47
CONEXIONES						
Tubería refrigerante	Líquido - Gas	Pulg.	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	1/4" - 5/8"
	Longitud máx.	m	20	20	25	25
	Desnivel máx.	m	10	10	10	10
Conexiones eléctricas	Alimentación eléctrica	mm	2 + T x 2,5	2 + T x 2,5	2 + T x 2,5	2 + T x 2,5
	Conexión	mm	3 + T x 2,5	3 + T x 2,5	3 + T x 2,5	3 + T x 2,5
CÓDIGO EAN	Conjunto		8435483828001	8435483827998	8435483827981	8435483827974

* Filtros incluidos: HEPA + Vitamina C + Fotocatalítico